

REFRIGERANT TYPE AIR DEVICE

ORIGINAL MODEL	Maximum Working Pressure (bar)	*CAPACITY			Voltaj	Filter Model	Connection Dimensions	Refrigerant Gas	Pressure Drop (mbar)
		m3/min	m3/h	cfm.					
WPS - 1200	16	1,2	72	42,4	230/1/50-60	F-014	3/4"	R-134a	205
WPS - 1800	16	1,8	108	63,6	230/1/50-60	F-018	3/4"	R-134a	220
WPS - 2200	16	2,2	132	77,7	230/1/50-60	F-018	3/4"	R-134a	250
WPS - 2800	16	2,8	168	98,9	230/1/50-60	F-030	1"	R-134a	220
WPS - 3800	16	3,8	228	134,2	230/1/50-60	F-040	1"	R-134a	310
WPS - 4800	16	4,8	288	169,5	230/1/50-60	F-060	1" 1/2	R-134a	250
WPS - 5500	16	5,5	330	194,2	230/1/50-60	F-060	1" 1/2	R-134a	310
WPS - 6500	16	6,5	390	229,5	230/1/50-60	F-075	1" 1/2	R-134a	330
WPS - 7800	16	7,8	468	275,5	230/1/50-60	F-075	2"	R-134a	300
WPS - 8500	16	8,5	510	300,2	230/1/50-60	F-110	2"	R-134a	320
WPS - 11000	16	11	660	388,5	400/3/50-60	F-110	2"	R-134a	320

(*40°C - Login 7bar, 25° Maximum Flow at Ambient Temperature)



Discover our product ranges at noitech.com